#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization

International Bureau



### - 1 CERTA DI CONTRO IN CONTRO DELLA CONTROLE DEL CONTROLE DEL CONTROLE DEL CONTROLE DEL CONTROLE DEL CONTROLE

#### (43) International Publication Date 3 June 2004 (03.06.2004)

#### **PCT**

## (10) International Publication Number WO 2004/045933 A2

LTD. [JP/JP]; 6-3 Ohsaki 1-chome, Shinagawa-ku, Tokyo

(51) International Patent Classification<sup>7</sup>: G01P 3/44

B60T 8/00,

2003-365350 2003-366354

141-8560 (JP).

24 October 2003 (24.10.2003)

) ЛР

\_\_\_\_\_

1-10

(21) International Application Number: PCT/JP2003/014532

(71) Applicant (for all designated States except US): NSK

27 October 2003 (27.10.2003)

003) JP

(22) International Filing Date:

14 November 2003 (14.11.2003)

14 1

English

(25) Filing Language:

(26) Publication Language:

. . . .

English

(30) Priority Data:

2002-334105	18 November 2002 (18.11.2002)	JP
2002-338366	21 November 2002 (21.11.2002)	JP
2002-342640	26 November 2002 (26.11.2002)	JP
2003-011459	20 January 2003 (20.01.2003)	JP
2003-016601	24 January 2003 (24.01.2003)	JP
2003-024355	31 January 2003 (31.01.2003)	JP
2003-026419	3 February 2003 (03.02.2003)	JP

(72) Inventors; and


(75) Inventors/Applicants (for US only): ISHIKAWA, Hiroaki [JP/JP]; c/o NSK Ltd., 5-50, Kugenumashinmei 1-chome, Fujisawa-shi, Kanagawa 251-8501 (JP). NAKAGOME, Yoshifumi [JP/JP]; c/o NSK Ltd., 5-50, Kugenumashinmei 1-chome, Fujisawa-shi, Kanagawa 251-8501 (JP).

(74) Agents: OGURI, Shohei et al.; Eikoh Patent Office, 28th Floor, ARK Mori Building, 12-32, Akasaka 1-chome, Minato-ku, Tokyo 107-6028 (JP).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

[Continued on next page]

(54) Title: AXLE UNIT WITH SLIP SENSOR AND SLIP MEASUREMENT METHOD



(57) Abstract: An axle unit 210 including a rolling bearing unit attached to a knuckle of a wheel support member has a slip sensor (211) including acceleration sensors and a rotation sensor in one piece. The slip sensor (211) has the rotation sensor placed on the base face, and the rotation sensor is placed facing an encoder (213) attached to a rotation member (212). At the vehicle running time, the traveling acceleration in the traveling direction of the wheel and the rotation angular speed are detected and at the vehicle running time, the ground speed of each wheel, the tire radius of each wheel, and the slip ratio of each wheel are found.



CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.